



OPTIME Ecosystem

Predictive Maintenance Made Easy
Condition Monitoring & Smart Lubrication

We pioneer motion

SCHAEFFLER

AVOID UNPLANNED DOWNTIMES THE EASY WAY. CONDITION MONITORING AND SMART LUBRICATION IN ONE SOLUTION.

Contents

Added value	4
Avoid Unplanned Downtime	4
Simplify Maintenance	5
<hr/>	
Overview of Solution Elements	6-7
OPTIME App	8-9
User Interfaces	10
Cloud & Analytics	11
Mesh Network	11
Cybersecurity	11
Digital Services – Mandatory	12
Digital Services – Optional	13
Expert Services	14
Hardware Components	15
OPTIME Condition Monitoring	15
OPTIME Smart Lubrication	15
OPTIME Gateway	15
<hr/>	
OPTIME Condition Monitoring Applications & Operating Modes	16-17
<hr/>	
Product Specifications	18-20
<hr/>	
Customer Testimonials	21
<hr/>	

Added Value

Avoid Unplanned Downtime

Avoiding unplanned machine downtimes and the costs associated with them, which can run to more than 100,000 euros an hour, is a challenge faced by companies in many different industries. Manual checks and relubrication tie up personnel and conceal risks, especially for hard-to-reach machines in harsh environments.

The OPTIME Ecosystem provides a solution to these problems by offering an easy way to implement predictive maintenance. This makes it a central component of Lifetime Solutions.



Schaeffler Lifetime Solutions
The Lifetime Solutions portfolio has a comprehensive range of products, services, and solutions for industrial maintenance. It is designed to support maintenance personnel over the entire service life of a machine and can be used in any industry.

medias.schaeffler.de/en/lifetime-solutions



Added Value

Simplify Maintenance

[> CONTENTS](#)



OPTIME is the world’s leading ecosystem for condition monitoring and lubrication. The solution has been successfully used for years in numerous sectors and has won multiple awards. Customers from all industries can begin monitoring and lubricating hundreds, or even thousands, of machines at each plant in just a few days and save money in unplanned downtime equivalent to many multiples of the investment every year. We are constantly adding new functions and features to the solution. In other words,

the OPTIME Ecosystem never sleeps.

What you can expect from the OPTIME Ecosystem

1

Easy installation

Hundreds of sensors or lubricators can be installed and set up on machines in just a few days.

2

Global number one

The OPTIME Ecosystem is the world’s leading solution for predictive maintenance and smart lubrication.

3

Easy scalability

The Ecosystem can be scaled at any time. A new plant has been connected every workday since 2023.

4

Value for money

The exceptional price-to-performance ratio makes the solution an easy choice for decision makers.

5

Fast payoff

Investment costs are proven to be recouped within 1–10 months thanks to fewer unplanned machine downtime.

6

Intelligence

AI analyses enable prompt fault detection and rectification.

7

Customer orientation

The OPTIME Ecosystem was developed based on direct user feedback and is constantly being improved.

8

Focus on service

Our team is available at all times to give you the support you need – including training.

9

Safety

Less time spent in hazardous areas results in fewer accidents and enhanced safety.

ACHIEVE TARGETS


Reduce with ...

Condition Monitoring unplanned downtime by up to **80%**

Smart Lubrication grease consumption by up to **30%**

OPTIME Ecosystem energy consumption by up to **3%**

The OPTIME Ecosystem comprises numerous elements and services that work together to reduce unplanned downtime. OPTIME Condition Monitoring and OPTIME Smart Lubrication are components of the intelligent OPTIME Ecosystem.



User Interfaces

With the user interfaces in the mobile OPTIME App, the OPTIME Dashboard (web-based), and the OPTIME [Expert-Viewer](#) (optional), users can easily access the information they need – anywhere, at any time.

Cloud & Analytics

With its high computing power and capacity, the OPTIME Cloud & Analytics component captures huge amounts of data and prepares them for easy understanding and processing.

Mesh Network

Connection of all OPTIME Ecosystem devices via the gateways – the automated, self-healing OPTIME Mesh Network configures itself, requires little energy, and offers a very large coverage area.

REST-API

The OPTIME REST API makes it easy to connect the OPTIME Ecosystem to other existing systems and get the most out of the data collected. Existing customer ecosystems may include maintenance and asset management systems, databases, and other elements.

Connector Service

With the OPTIME Connector Service, you can easily connect SmartCheck, ProLink CMS, and other devices to the OPTIME Ecosystem.

Expert Services

Expert Services complement the OPTIME Ecosystem with key services such as integrated in-app access to vibration experts, training, and support offerings to help you get the most out of your OPTIME Ecosystem.

Condition Monitoring

With wireless vibration sensors, you can monitor your machines, even in hazardous areas, from wherever you are.

- OPTIME 3
- OPTIME 5
- OPTIME 5 Ex

Smart Lubrication

Simplify lubrication

- With the world's first intelligent lubricator, the OPTIME C1.
- OPTIME C1 Adapter, used in conjunction with the OPTIME C1, turns existing, gas-powered lubricators into smart devices.

Gateway


The OPTIME Gateway collects data from OPTIME vibration sensors and lubricators. It is a standalone device that makes secure cloud connectivity easy without requiring integration into your IT/OT networks and can also be used in hazardous areas up to Zone 2/21.

Overview of Solution Elements

OPTIME App


The app shows key information from the OPTIME Dashboard, such as the machine status and alarms, in an optimal way for mobile use. With the app, you can access information even when you are situated at the machine. In addition, you can add information from the machine. You can easily organize the sensors and lubricators on all your machines with the help of group or machine management. Find out how the mobile app works below.

The Schaeffler OPTIME App can be downloaded from the [Apple App Store](#) or [Google Play](#).

Schaeffler OPTIME

Group management

- Machine health status
 - Severe: Machine exhibits advanced damage. These machines should be inspected and, if necessary, repaired.*
 - Warning: Inspect the machine and schedule repairs for the next regular maintenance date.*
 - Suspect: No immediate response is required.*
- All lubricators: In this group, the statuses of all lubricant sensors are displayed. In addition to the filling level and the remaining time until the cartridge needs to be changed, problematic operational statuses with respect to lubrication are displayed.
- Battery status: Sensors or lubricators with low battery levels are shown here.
- Reception status: Sensors or lubricators that are offline and have not transmitted any data in the last 24 hours are shown here.



My groups


Below the alarm-based groups are the individual user-defined groups, which can be created very easily.

Examples

- Local conditions (location, building)
- Production-relevant structures (segments, product lines, production units)
- Machine types (motors, fans, pumps)


Machine management

- Track machine status
- Acknowledge alarm notifications
- Edit machines
- View and add notes to machine log
- Navigate to subordinate sensors or lubricators
- Add new sensors or lubricators
- Request expert analyses




Sensor management OPTIME Condition Monitoring

- Acknowledge alarm notifications
- View KPIs
- View raw data
- Edit sensors
- Request new KPIs and raw data
- View and add notes to machine log



Smart Lubricators

- View and acknowledge alarm notifications
- View status information
- View cartridge information
- Edit lubricator and outlet names
- Change dispensing settings
- Change lubricant cartridge
- Reactivate lubricator
- Deactivate lubricator
- Show notes



Overview of Solution Elements

User Interfaces


With the user interfaces in the intuitive mobile OPTIME App, the OPTIME Dashboard, and the OPTIME [ExpertViewer](#), users can easily access needed information at any time, regardless of their location or function.

What the OPTIME dashboard offers

- Start screen showing complete overview of plant at a glance
- Intuitive control functions for easy and fast navigation
- Search function for easy finding of all machines and assets
- Uniform user interface and user experience across all devices (including tablets)
- Special user and asset management for administrators

Browser

- Google Chrome
- Microsoft Edge
- Mozilla Firefox
- Safari
- Microsoft Internet Explorer



Find important functions quickly

- 1 Access to OPTIME management functions and to user instructions and manuals
- 2 Quick view showing all warnings and alarms coming from the user's device at a glance
- 3 These special groups deliver the operational statuses and data for the sensors and lubricators, e.g., sensors and lubricators that have low battery levels, have not recently received data, or are in learning mode.
- 4 Automatically created user plant structure for easy visualization of status of each department or individual area and fast localization of problems.

Functions for administrators only

- User management
 - Add, edit, and delete users and profiles
 - Send notifications to users
- Asset management
 - Add, move, and delete gateways, sensors, and lubricators

Overview of Solution Elements

Cloud & Analytics, Mesh Network, Cybersecurity

Apart from the user interfaces, there are two main technical components of the OPTIME Ecosystem Digital Services: Cloud & Analytics and the Mesh Network.

Cloud & Analytics

The OPTIME Cloud & Analytics platform helps companies manage large amounts of data and gain valuable insights from them. The high computing power of the platform makes fast processing of data streams collected from various sources possible.


A central aspect of OPTIME Cloud & Analytics is its ability to prepare data. State-of-the-art algorithms filter, clean, and structure the raw data, thereby providing the basis for reliable analyses.

The platform uses advanced analytical tools to identify patterns and trends in the data. The platform uses advanced analytical tools to identify patterns and trends in the data, supplemented by specific evaluation logic based on decades of experience of vibration experts. OPTIME Cloud & Analytics visualizes the data. Thanks to clear dashboards and interactive reports, users can gain an understanding of complex data without requiring any in-depth knowledge of vibration analysis.



Mesh Network

OPTIME communication is based on the licensed Wirepas mesh (WM) technology. It is a decentralized wireless communication protocol for IoT devices. Due to the unique decentralized operation, the device nodes contain the entire network intelligence. The devices themselves make all decisions locally and cooperatively, e.g., about the choice of adjacent node, the transmission power, and the frequency channel. This makes reliable, scalable, and user-friendly connectivity for devices possible with no interference with neighboring networks. Each node is a redistribution point in the mesh network, resulting in greater network coverage and seamless communication with no dead zones, even in hard-to-reach spots.



Cybersecurity

- Cybersecurity based on proven best practices and leading standards such as IEC 62443 4-2 and the OWASP ASVS framework
- Dedicated secure areas for all customers to keep data separate during both transmission and storage
- Customer data are protected through encryption both during transmission and during storage. Secure transmission protocols such as HTTPS, SFTP, VPN, and TLS 1.2 are used. AES-256 is used for encryption during storage.
- IEEE 802.1AR IDevID Secure Device Identity for OPTIME IoT Edge Devices ensures device integrity from production throughout the entire life cycle using a global independent and trusted certification authority.
- Long-term protection and life cycle are ensured by a validity of 50 years per IDevID certificate issued and an RSA key length of 4096 bits.



Digital Services Mandatory

The OPTIME Digital Service forms the basis for the OPTIME Ecosystem. This cloud-based solution can be used via mobile apps and web apps for desktop browsers in such places as control rooms or at workstations. After the customer has subscribed to the Digital Service, a separate area in the Schaeffler Cloud is created specifically for the customer and the customer is granted access to the Digital Service. Management of the OPTIME installation is done via the mobile app or the OPTIME Dashboard. OPTIME Digital Service comprises basic as well as optional service components.

Digital Base Fee

- Access to OPTIME Dashboard and App
- Unlimited number of users
- Training Campus
- Provision of and access to customer-specific area in the Schaeffler Cloud
- User access and management
- Commissioning and activation of sensors and gateways via the mobile app
- Note: Schaeffler requires the name and an email address of at least one main user from the customer’s organization in order to create the subscriber.
- After the order has been successfully processed, the customer sets up the subscription and is invoiced for it at the beginning of the following month.
- The customer is informed by email of the successful setup.
- Any minimum contract periods agreed on start on the 1st of the month of the first invoice.

Digital Service Analytics

- Vibration-based automated condition assessment of monitored machines using algorithm-based automated diagnostics
- Display of alarms and root causes of failures
- Fees are only charged for active sensors. A sensor is active as soon as the Schaeffler Cloud receives measurement data from the sensor.
- If Schaeffler shipped a gateway with a SIM card, the data transfer costs are included in the monthly fees.*
- Note: Schaeffler only needs the monitored machine type for the automated analysis and alarms. Other optional metadata (criticality, machine ISO class, and more) can be included to yield better results.

Digital Lubrication Management

- Display of status information for the OPTIME Smart Lubricator devices (e.g., filling level, battery status, or number of days before cartridge change is required)
- Generation and display of alarms (critical lubricant level, exceeded temperature limits, excessively high backpressure)
- Identification of root causes of faults
- Support in selection of lubricant and relubrication parameters
- Remote change of lubrication settings
- Fees are only charged for active devices. A device is active as soon as Schaeffler OPTIME Cloud receives data from the device.
- If Schaeffler shipped a gateway with a SIM card, the data transfer costs are included in the monthly fees.*


** Your Schaeffler contact will be happy to answer any questions you may have regarding prices.*

Digitale and Expert Services Optional

OPTIME ExpertViewer

The digital service OPTIME ExpertViewer offers an extensive collection of analysis tools for manual depth analysis and root cause analysis. Vibration data and data from lubricators can be evaluated with them. The service can be used with all OPTIME-compatible data, including Schaeffler SmartCheck and Schaeffler ProLink CMS. The ExpertViewer is optimized for the high-performance analysis of large amounts of vibration data. Handling is easy. Users log in with the user data for OPTIME.

Good to know: The number of users on the customer side for the ExpertViewer digital service is not limited. Monthly fees are charged for this service. The OPTIME ExpertViewer is provided as a download and requires an active Digital Service subscription.



Digital Service REST API

With this service, OPTIME data can be made accessible via a software interface. You receive access to raw vibrations and raw KPI values (for each sensor) as well as machine status, pending/active alarms, and alarm history (for each machine). You can also view information such as when the cartridge needs to be changed as well as the filling level, status, and any alarms/warnings for each of the lubricators. Data access rates are limited by the API proxy. The rate limits protect the OPTIME Condition Monitoring system from deliberate or accidental misuse via the API. Schaeffler requires at least one lead developer from the customer’s organization as a contact person, who receives access to the Schaeffler API Developer Portal. The designated lead developer is provided with access and introductory information. Monthly fees are charged for this service. The service is accessed through the Schaeffler Developer Portal. This guarantees the state-of-the-art security and protection of the system.

Connector Service

With the OPTIME Connector Service, you can easily connect SmartCheck, ProLink CMS, and other devices to the OPTIME Ecosystem. As a result, these Condition Monitoring systems are also able to use the intelligence and advantages of the OPTIME Ecosystem.

The Connector Service ensures that devices with different communication protocols and data formats can communicate with each other. The Connector enables real-time processing of data through standardized APIs.

In a few words, the OPTIME Ecosystem as a central platform enables the monitoring and management of all connected devices and data streams, which greatly facilitates maintenance and support. The interface is provided. Monthly fees are charged based on usage.

Single Sign-On Activation

OPTIME Single-Sign-On (SSO) Activation is available as an add-on service for the OPTIME solution.

SSO authentication makes for a smoother user experience. OPTIME users authenticate only once with their company login data and without any other OPTIME-specific login data. With just one set of login data to access multiple applications, users no longer need to remember multiple passwords. In addition, the risk of password theft is reduced. The default method for SSO authentication in OPTIME is to use Open ID Connect (OIDC) protocols and configure a specific AD group for administrators, operators, and viewers for each organization.

SSO activation enables the central management of OPTIME users in a central identity provider solution by the customer’s IT department. This means you can rely on the company’s preferred password checks and even multifactor authentication if this is required by company policy.

If you are interested in this service, please get in touch with your Schaeffler contact, who will connect you to a Schaeffler specialist to discuss details.

If your schedule is full, you're under time pressure, or you need more maintenance personnel, you can be sure of one thing:

WE ARE THERE RIGHT FROM THE START – THE FIRST MONTH ...


... and we mean personally there, despite our love of automation. Our journey together can begin; our common aim is to avoid unplanned downtimes. In the first month, we plan the OPTIME rollout all the way to installation. The doors to the OPTIME Ecosystem, the Training Campus, and the technical product support from our experts open for you.

FOR 6 MONTHS, WE ARE YOUR BODYGUARD ...

... and are there to offer you advice during and after the installation of your OPTIME system. During this six-month phase, we regularly invite you to participate in a team call, for example, to discuss the statuses of your assets and to provide clarification, for example, on how to interpret the measurement results.

AFTER 7 MONTHS, YOU DECIDE ...

... how you want to continue using the Expert Service. We offer three different options for this. Our goal is to give you as much support as you need. And don't worry you can switch to another service package at any time if you need additional services.



INSTALLATION PHASE

- Services
- Project planning
 - Subscription setup
 - Account creation
 - Access to Schaeffler Online Training Campus
 - Practical installation support
 - OPTIME device mounting service (optional)

ACCOMPANIMENT PHASE

- Services
- Regular data analysis by experts
 - System checking and maintenance
 - Consultations with Schaeffler experts
 - Alarm management and fine-tuning
 - Added value documentation
 - Access to condition monitoring experts

SCALE-UP-PHASE

- After 7 months, you can continue on your own or continue to rely on our experts. You can use our Expert Service as follows.
- Expert Service on request
 - Regular data analysis by experts

TRAININGS

You get free access to the OPTIME Condition Monitoring and OPTIME Smart Lubrication basic training courses. [> more](#)



OPTIME Condition Monitoring

OPTIME Condition Monitoring is an easy-to-scale condition monitoring solution within the OPTIME Ecosystem. It was developed to serve a variety of purposes in industry and is recommended for series of rotating machines with speeds of 120*–5000 rpm. It minimizes user efforts for each individual process step. This makes OPTIME Condition Monitoring particularly suitable for condition-based monitoring of large numbers of machines, even in hazardous areas.

OPTIME 3, 5 and 5 Ex Sensors

The battery-operated sensors can be quickly and easily mounted on the machines and record vibration and temperature data for the monitored unit.

- 1 OPTIME 3: Recommended for machine speeds of 120 rpm* to 3000 rpm
- 2 OPTIME 5: Recommended for machine speeds of up to 5000 rpm
- 3 OPTIME 5 Ex: Extends range of use cases to include hazardous areas

Applications & Modes

Typical machine combinations [> more](#)
Modes: Standard, Dynamic, High Dynamic [> more](#)

7 OPTIME Gateway

OPTIME Gateway and OPTIME Gateway Ex are standalone devices that enable secure cloud connectivity. They process data from OPTIME vibration sensors and lubricators.

OPTIME Smart Lubrication

The OPTIME C1 Smart Lubricator is designed to simplify lubrication, minimize rounds, and supply hundreds of lubrication points. It is an easy-to-use and economical solution for automatic single-point lubrication. OPTIME C1 adds Smart Lubrication to the OPTIME Ecosystem. This allows users to identify relationships between machine condition and lubrication in one comprehensive solution.

OPTIME C1, CONCEPT1 and Adapter

- 4 OPTIME C1 can be screwed directly onto a lubrication point or connected to a lubrication line.
- 5 A cartridge CONCEPT1 serves as a lubricant reservoir. The possible term setting can be from 1 month to 12 months.
- 6 The cartridge adapter allows certain lubrication devices from other manufacturers to use the intelligent lubrication of the OPTIME C1. [> more](#)

* Application-specific

OPTIME Condition Monitoring Applications

The OPTIME solution offers different modes (Standard, Dynamic, Highly Dynamic) to allow adaptation to the duty cycle of the machine. See the following page for more information.

For OPTIME 3 sensors, machine speeds of 120 rpm* to 3000 rpm are recommended, and for OPTIME 5 sensors, machine speeds of up to 5000 rpm are recommended; in addition, the sensor variant OPTIME 5 Ex makes it possible to extend this use case to cover hazardous areas. When choosing a suitable combination of machines and sensor, it is important to consider a few factors (see table).

Typical combinations of machines and sensors

Application	Characteristic	Sensor		Mounting location
Electric motor	< 0,5 m	OPTIME 3	1	<ul style="list-style-type: none">Bearing position on the drive side of the motorCentral on the engineIn the middle at the foot of the motor
Electric motor	> 0,5 m	OPTIME 3	2	<ul style="list-style-type: none">Drive side and non-drive side of the motorFoot from drive side and non-drive side of the motor
Fan	overhang	OPTIME 3	1	<ul style="list-style-type: none">Plummer block housing
Fan	between the bearing	OPTIME 3	2	<ul style="list-style-type: none">Plummer block housing
Fan	directly coupled	OPTIME 3	1	<ul style="list-style-type: none">Drive side of the motor
Compressor	–	OPTIME 5	2	<ul style="list-style-type: none">Bearing location
Pillow block	–	OPTIME 3	1	<ul style="list-style-type: none">Bearing location
Pump	–	OPTIME 5	2	<ul style="list-style-type: none">Bearing location
Gear motor	< 0,5 m	OPTIME 5	1	<ul style="list-style-type: none">Bearing location
Gear motor	> 0,5 m	OPTIME 3	1	<ul style="list-style-type: none">Motor
Gear motor	> 0,5 m	OPTIME 5	1	<ul style="list-style-type: none">Gearbox
Extruder	–	OPTIME 3	2	<ul style="list-style-type: none">Bearing location
Calander	–	OPTIME 3	2	<ul style="list-style-type: none">Bearing location
Belt drive	–	OPTIME 3	2	<ul style="list-style-type: none">Bearing location
Saw	–	OPTIME 5	1	<ul style="list-style-type: none">Bearing position of the saw blade
Shaft	–	OPTIME 3	1	<ul style="list-style-type: none">Bearing housing
Gearbox	–	OPTIME 5	2	<ul style="list-style-type: none">Input and output


* Application-specific

OPTIME Condition Monitoring Operating Modes

To ensure reliable machine monitoring for all types of machines, OPTIME Condition Monitoring offers three different mode settings. The best battery life is achieved in Standard mode. In Dynamic and Highly Dynamic modes, the OPTIME sensor learns to detect when the machine is in operation and performs measurements only in this state.


Standard Mode (STM)

Sensors measure at fixed time intervals.
Suitable for machines that run continuously for at least 4 hours.




Dynamic Mode (DM)

Dynamic measurements for machines that operate only occasionally but run continuously for more than 30 seconds.



High Dynamic Mode (HDM)

Dynamic measurements for machines that are operated only occasionally and are active for at least 5 seconds to about 30 seconds.



Use Case – HDM




A customer uses HD mode for container cranes and was able to detect developing bearing damage at an early stage. Unplanned downtime and expensive consequential damage were prevented.



»Scan or click on [link](#) to find out more

Product Specifications

OPTIME Condition Monitoring

OPTIME CM sensors	OPTIME-3 	OPTIME-5  OPTIME 5 Ex 
Vibration bandwidth	2 Hz – 3 kHz	2 Hz – 5 kHz
Amplitude range	±2/±4/±8/±16 g	±2/±4/±8/±16 g
Temperature trend measurement	–40°C to +85°C	–40°C to +85°C
Calculated KPIs	RMS _{Low} , Kurtosis _{Low} , ISO _{VELOCITY} , RMS _{High} , Kurtosis _{High} , DeMod, Temperature	RMS _{Low} , Kurtosis _{Low} , ISO _{VELOCITY} , RMS _{High} , Kurtosis _{High} , DeMod, Temperature
Measurement cycle	KPIs: 6x per day Time waveform: every 24 h	KPIs: 6x per day Time waveform: every 24 h
Typical target applications	Motors, generators, fans, pillow block bearings, up to 3.000 rpm	Pumps, geared motors and small gearboxes, compressors, HVACs etc., up to 5.000 rpm
Sensor commissioning	NFC (Near Field Communication)	NFC (Near Field Communication)
Communication	Wirepas Mesh (2.4GHz ISM Band)	Wirepas Mesh (2.4GHz ISM Band)
Sensor transmission range (line of sight)	up to 100 m	up to 100 m
Power supply	Non-replaceable Li-SOCl ₂ battery	Non-replaceable Li-SOCl ₂ battery
Typical battery life	up to 5 years (depending on configuration)	up to 5 years (depending on configuration)
Operating temperature range	-40° to +85°C	-40° to +85°C
Recommended storage temperature (for optimum battery life)	0° to 30°C	0° to 30°C
Ingress protection	IP 69K	IP 69K
Materials	Mounting base: steel AISI 316, housing: Polycarbonate	Mounting base: steel AISI 316, housing: Polycarbonate
Mounting	Single Bolt Mounting (M6) (Adapters available)	Single Bolt Mounting (M6) (Adapters available)
Dimensions	Please see drawings	
Certifications	CE, ANATEL, ANRT, COC, CRC, FCC, IC, ICASA, IFETEL, IMDA, KC, MIC, MOC, NBTC, NCC, NTC, RCM, SDPPI, SIRIM, SRRC, SUBTEL, TDRA, UKCA, WPC	
Hazardous areas	ATEX/IECEx Zone 1/21 For details please see sensor markings. CCC, CSA, ECAS Ex, INMETRO, KCs, MASC, PESO	

Product Specifications

OPTIME Smart Lubrication

Description		Value
OPTIME C1 function		
Drive system		Electro-mechanical
Operating pressure		< 10 bar
Metering volume per lubrication interval		0,5 cm³
Metering volume per day (dependent on size and setting of CONCEPT1)		0,17 up to 8,3 cm³
Commissioning		NFC
OPTIME C1 lubricator		
Dispensing time (steplessly adjustable)		1 up to 12 months
Lubricant volume		60, 125, 250* cm³
Lubricant	Grease	< NLGI 2
	Oil	> 68 mm2/s
Communication		
Wirepas Mesh (ISM band)		2,4 GHz
Range with line of sight		100 m
Electrical characteristics		
Power supply (battery pack)		6 V
		2,3 Ah
Other characteristics		
Mounting position		As required
Threaded connector		G¼
Housing material		PET
Mass		0,25 kg
Packing unit		10 pieces
Ambient conditions		
Protection class		IP68
Operating temperature		–10 up to +55 °C
Storage (protect from direct sunlight, store in a dry place)	Temperature (recommended)	+20± 5 °C
	Humidity	< 65 %
Certifications		
Link		–


* with suitable cartridges from other manufacturers



Overview of key functions:

- Status and level information available via OPTIME App or Desktop Dashboard
- Automatic alarm notification for incidents
- Easy installation and maintenance
- Possibility of setting each lubricator individually
- Optimized maintenance and routing
- Operating pressure of up to 10 bar
- Quick and easy replacement of lubricant cartridge
- Multilingual user navigation


Product Specifications

OPTIME Ecosystem


Gateway	OPTIME Gateway (Ex)	OPTIME Gateway 2 (Ex)
Sensor communication	Wirepas Mesh (2.4 GHz ISM Band), maximum number of sensors: 50	Wirepas Mesh (2.4 GHz ISM Band), maximum number of sensors: 50
Sensor communication Schaeffler IoT Hub	2G, LTE CAT M1 LTE-Stick: GSM, UMTS, LTE (default) Wi-Fi 2.4GHz, Ethernet RJ45	LTE, UMTS, GSM (integrated) Wi-Fi 2.4GHz, Ethernet RJ45
SIM card format	Micro-SIM (3FF) depending on LTE stick	Micro-SIM 3FF
Ingress protection	IP 66/67 (standard) IP 66, Nema 4X (Ex)	IP 66, Nema 4X (standard and Ex)
Protection class		
Operating temperature	-20°C bis 50°C (standard) -20°C bis 55°C (Ex)	-20°C bis 70°C (standard) -20°C bis 55°C (Ex)
Storage temperature	-40°C to 85°C Humidity 20 ... 90 °C	-40°C to 85°C Humidity 20 ... 90 °C
Power supply	Voltage range 85-264VAC, 47-440Hz, Power consumption 30VA max.	Voltage range 100 ... 240 VAC (±10 %), 50/60 Hz Alternative voltage range 12 VDC (±10%) Power consumption 20 VA
Certifications	CE (EU Directive 2014/53/EU), ANATEL, ANRT, COC, CRC, FCC, IC, ICASA, IFETEL, IMDA, KC, MIC, MOC, NBTC, NCC, NTC, RCM, SDPPI, SIRIM, SRRC, SUBTEL, TDRA, WPC	CE (EU Directive 2014/53/EU), FCC conform, further certifications will follow
Certifications(Ex)	ATEX/IECEX Zone 2/21 Further details are available on the device label CCC, QPS, ECAS Ex, INMETRO, KCs, MASC, PESO	ATEX/IECEX Zone 2/21 Further details are available on the device label CCC, QPS, ECAS Ex, INMETRO, KCs, MASC, PESO



Dimensions of the OPTIME Gateway



Dimensions of the OPTIME Gateway 2



Dimensions of the OPTIME Gateway Ex and OPTIME Gateway 2 Ex

Customer Testimonials

[» CONTENTS](#)



“I never thought the installation of 100 sensors would be so easy and fast.

I had planned three days for the installation, but the work was already done in 14 hours.

OPTIME was so easy to set up that I sent the Schaeffler employees home sooner than expected!”

Carmelo Hernandez
Maintenance Manager
Heidelberg Materials (formerly Lehigh Hanson)



“OPTIME C1 lets us know early enough if the points are not lubricated or the lubrication point is empty.

When I open the app and see that everything is running smoothly, it gives me peace of mind.”

Peter Hannappel
Maintenance Manager
Westerwälder Elektro Osmose



“OPTIME helped us avoid unplanned downtimes and saved us more than US\$920,000.

I love the ease of installation, ease of use, and the really cool OPTIME Dashboard. It's great that you always have everything in view.”

Ryan Miernicki
Reliability Engineer
Acme Corrugated Box

FURTHER INFORMATION



Technical details
on OPTIME Condition
Monitoring
› Scan QR code
› Click on [link](#)



Technical details
on OPTIME C1
› Scan QR code
› Click on [link](#)




More Information
on the Expert Service
› [E-Mail us](#)





Request the
Cybersecurity document
› [E-Mail us](#)

OPTIME Condition Monitoring In Action



OPTIME Smart Lubrication In Action



Schaeffler Technologies AG & Co. KG

Georg-Schäfer-Straße 30
97421 Schweinfurt
Germany

medias.schaeffler.de/en/lifetime-solutions
lifetime.solutions@schaeffler.com

Phone +49 2407 9149-66

Every care has been taken to ensure the correctness of the information contained in this publication but no liability can be accepted for any errors or omissions. We reserve the right to make technical changes. This publication supersedes all deviating information from older publications.
© Schaeffler Technologies AG & Co. KG
Issued: February 2025, Version 01
This publication or parts thereof may not be reproduced without our permission.